

EXPLORER 710

High-Speed, Portable and Powerful BGAN Terminal

Product Sheet

COBHAM
SATCOM
Connecting the future



EXPLORER 710

High-Speed, Portable and Powerful BGAN Terminal



Raising the BGAN bar

EXPLORER 710 is a portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

Smallest and Lightest

The smallest and only full Class 1 BGAN terminal positioned to support broadcasters by enhancing the quality of mobile outside broadcasting.

Fastest ever BGAN

The first and only BGAN terminal to support the full High Data Rate on-demand streaming service from Inmarsat. With speeds averaging 650 kbps, the EXPLORER 710 sets a new standard for mobile video newsgathering.

Double the speed with Plug & Play bonding; simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

Smart and Easy

EXPLORER 710 introduces smart devices to the world of BGAN, enabling users to connect their own smart phone for terminal control, voice calls and connectivity. The EXPLORER Connect App is available on Android and IOS.

Other features include a USB host interface, hot-swappable batteries, a large easy-to-use LED display and multiple interfaces to support a wide range of applications.



Specifications

Dimensions	
Total H / W / D:	332 / 279 / 54 mm 13.07 / 10.98 / 2.13 inches
Total weight:	
Antenna:	3.5 kg / 7.7 lbs (incl. battery)
Transceiver (incl. battery):	1.9 kg / 4.2 lbs
Global Services	
Voice:	4 kbps AMBE+2
Premium voice:	3.1 kHz audio, 64 kbps
Standard IP:	Up to 492 kbps
Streaming IP:	32, 64, 128 kbps (256 kbps & BGAN X-Stream)
HDR Streaming:	Min. 600 kbps Min. 300 kbps (1/2 channel HDR)
ISDN:	UDI 64 kbps / RDI 56 kbps
SMS:	Not supported
Inmarsat frequencies:	
	1518.0 - 1525.0 MHz (Rx) (EMEA)
	1525.0 - 1559.0 MHz (Rx)
	1626.5 - 1660.5 MHz (Tx)
	1668.0 - 1675.0 MHz (Tx) (EMEA)
EIRP:	20dBW ±1dB
User Interface:	
	PMOLED Display, 5 navigation keys, Audio and LCD pointing aids and LED indicator, Compass
Languages:	UK, FR, DE, ES, RU and CN
Approvals:	Inmarsat Class 1 Type Approval at launch CE & FCC at launch. Other approvals TBC

Interfaces

1 x Analogue RJ-11 phone/fax interfaces	
2 x LAN (RJ-45) interface	
Power over Ethernet:	PoE Cl. 2 on one RJ-45 interface
Max. cable length:	100m / 328ft (Cat5 UTP)
1 x USB host interface	
2.0 (host), Charging up to 2A	
1 x ISDN interface	
Connector type:	RJ-45
Max. units per port:	8, max. total power supplied 1W
1 x Transceiver / Antenna interface	
Connector type:	TNC-TNC
Max. cable loss:	1.4 / 20dB @ 1.5GHz

1 x BGAN SIM-Card slots	
WLAN Access Point	
Standard:	IEEE 802.11 b/g

Environmental conditions

Temperature	
Operational (ambient):	-25°C to +55°C / -13°F to +131°F
Storage (excl. battery):	-40°C to +80°C / -40°F to +176°F
Battery storage temperature	
1 month:	-20°C to +60°C / -4°F to +140°F
3 months:	-20°C to +45°C / -4°F to +113°F
1 year:	-20°C to +20°C / -4°F to +68°F
Water and dust:	Transceiver: IP52 / Antenna: IP66
Relative humidity:	95% non-condensing at +40°C / +104°F

Power

DC input range:	
	10-32VDC
Power consumption	
Intelligent Power Management 65W (max.)	
AC/DC power supply	
Input:	100-240VAC, 47-63Hz, 65W
Output:	19VDC
Connector type:	2.5 / 5.5 mm power jack
Battery:	
Lithium ion, rechargeable	
Stand-by time:	36 hours
Transmit time, max.:	2h30m @ 144 kbps (25°C / 77°F)
	1h30m @ 650 kbps
Receive time, max.:	3h30m @ 492 kbps

Other features

Built-in SIP server
Embedded Webserver
Advanced Router with admin control
Wireless Access Point
Battery hot-swap and Built-in BGAN bonding
Remote activation and remote management

EXPLORER Connect App for IOS and Android:
Includes a SIP Softphone, Terminal Access to control your BGAN and Pointing Assistance.

EXPLORER Cellular Modem for USB:
With the EXPLORER LTE Modem you can connect local cellular networks and use the EXPLORER 510 as wireless router for all your devices.

Package

EXPLORER 710 Transceiver & Antenna incl. rechargeable lithium ion battery, Antenna cable, 2m ISDN/LAN cable, 115/230VAC power supply, Quick start guide.

Accessories

403686G	Lithium Ion Battery
403682P	100-240V AC/DC Power Supply
403650A-009	Car Charger Cable
403720B-010	Battery Hot Swap Cable
403756A-00500	EXPLORER Cellular USB Modem
403670A-00500	IP Handset incl. Cradle
403650A-921	Pole Mount Kit
403720B-050	Softshell case
403720B-942	10m Antenna Cable
403720B-945	30m Antenna Cable
403720B-947	50m Antenna Cable
403720B-953	80m Antenna Cable

Product number

403720B-00506	EXPLORER 710 Terminal
---------------	-----------------------



For further information please contact:
satcom.land@cobhamsatcom.com